

HBRE

Premium Round LED High Bay, 14,000 – 34,000 Lumens (100 – 240W)

STANDARD



FEATURES

- Available in 4000k (neutral white) and 5000k (cool white) color temperatures.*
- Long-life LEDs provide 174,000 hours of operation with at least 70% of initial lumen output (L₇₀).**
- Provides a range of 14,000 to 34,000 nominal lumens.*
- Universal 120-277 AC voltage (50-60Hz) and 6-foot incoming AC power cords are standard.
- 0-10vdc dimming drivers are standard.
- Watertight, compression-type electrical connectors.
- Mounting options include suspension from pre-installed mounting hook, yoke mounting, snap hook, and attachment to electrical conduit.
- Glass lens.
- Power factor ≥ 0.90 .
- Total harmonic distortion $\leq 20\%$.
- Color rendering index ≥ 80 .
- Die cast aluminum housing, painted black.
- Easy installation in new construction or retrofit.

WARRANTY & LISTINGS

- cULus listed for wet locations in ambient temperatures from 30°C to 50°C (-22°F to 122°F).
- DLC premium approved.
- IP66 rated for ingress protection.
- Complies with FCC Part 15, Class B.
- Complies with EN61000-4-5, surge immunity protection (4kV).
- 5-year warranty of all electronics and housing.

ORDERING INFORMATION

Example: HBRE-14L-5K


Model	Lumen Output		Color Temperature		Mounting Accessories (Order Separately)	
HBRE						
HBRE	14L	14,000	4K	4000k	LEDHBRN-PSH-PRM-V2	Pendant snap hook
	21L	21,000	5K	5000k	HBRE-YOKE-S	Yoke mount bracket (14L & 21L models)
	28L	28,000				
	34L	34,000			LEDHBRN-YOKE-PRM	Yoke mount bracket (28L & 34L models)



MOUNTING OPTIONS


- Suspension from pre-installed mounting eyebolt with locking set screw is standard.
- Ceiling-mounted installation (using optional yoke mounting bracket, provides up to 180° of adjustability).
- Two ways to mount luminaire to electrical conduit:
- Attach conduit (1/2" NPS) to optional yoke mounting bracket.
- Optional pendant snap hook

DIMENSIONS




Model	Diameter	Height	Weight
14L & 21L	11.7"	7.3"	6.8 lbs.


MOUNTING OPTIONS




**Ceiling-Mounted
(HBRE-YOKE-S)
(LEDHBRSN-YOKE-PRM)**



**1/2" Conduit-Mounted
(HBRE-YOKE-S)
(LEDHBRSN-YOKE-PRM)**



**3/4" Conduit-Mounted
(HBRSN-PSH-PRM-V2)**



Adjustable

ELECTRICAL DATA

Model	Color Temperature	CRI ¹	Luminaire Lumens	Luminaire Watts	Lumens/Watt	Input Voltage ²	Input Current (A)			Power Factor	THD ³	L ₇₀ Hours ⁴
							120V	240V	277V			
HBRE-14L-4K	4000k	>80	14,497	102	142	120-277	0.85	0.43	0.37	>0.90	<20%	174,000
HBRE-14L-5K	5000k	>80	14,864	102	146	120-277	0.85	0.43	0.37	>0.90	<20%	174,000
HBRE-21L-4K	4000k	>80	20,859	150	139	120-277	1.25	0.63	0.54	>0.90	<20%	174,000
HBRE-21L-5K	5000k	>80	21,406	150	142	120-277	1.25	0.63	0.54	>0.90	<20%	174,000
HBRE-28L-4K	4000k	>80	28,341	200	141	120-277	1.67	0.83	0.72	>0.90	<20%	174,000
HBRE-28L-5K	5000k	>80	28,948	200	145	120-277	1.67	0.83	0.72	>0.90	<20%	174,000
HBRE-34L-4K	4000k	>80	33,552	241	139	120-277	2.00	1.00	0.87	>0.90	<20%	174,000
HBRE-34L-5K	5000k	>80	34,240	241	142	120-277	2.00	1.00	0.87	>0.90	<20%	174,000

¹ Color rendering index.


² All 50-60Hz.

³ Total harmonic distortion.

⁴ L₇₀ refers to the number of hours at which lumen output declines to 70% of the initial level. L₇₀ hours are IES TM-21-11 calculated hours.

PHOTOMETRIC DATA

HBRE-14L-4K (14,497 Lumens)




Candlepower Summary

	°0	°90
°0	5,114	5,114
°10	5,019	5,004
°20	4,789	4,783
°30	4,410	4,404
°40	3,864	3,855
°50	3,154	3,144
°60	2,224	2,194
°70	1,172	1,145
°80	279	252
°90	12	24

Zonal Lumen Summary


Zone	Lumens	% Fixture
°10 – °0	483	3.3%
°20 – °0	1,873	12.9%
°30 – °0	4,007	27.6%
°40 – °0	6,620	45.7%
°50 – °0	9,364	64.6%
°60 – °0	11,823	81.6%
°70 – °0	13,529	93.3%
°80 – °0	14,281	98.5%
°90 – °0	14,380	99.2%
°180 – °90	117	0.8%
°180 – °0	14,497	100.0%

Cone of Light



PHOTOMETRIC DATA

HBRE-21L-4K (20,859 Lumens)




Candlepower Summary

	0°	90°
0°	7,363	7,363
10°	7,219	7,225
20°	6,907	6,916
30°	6,381	6,368
40°	5,589	5,593
50°	4,602	4,549
60°	3,296	3,198
70°	1,781	1,684
80°	451	371
90°	18	0


Zonal Lumen Summary

Zone	Lumens	% Fixture
0° – 0°	695	3.3%
0° – 10°	2698	12.9%
0° – 20°	5773	27.7%
0° – 30°	9536	45.7%
0° – 40°	13487	64.7%
0° – 50°	17028	81.6%
0° – 60°	19503	93.5%
0° – 70°	20610	98.8%
0° – 80°	20752	99.5%
0° – 90°	107	0.5%
0° – 180°	20,859	100.0%

Cone of Light



HBRE-28L-4K (28,341 Lumens)




Candlepower Summary

	0°	90°
0°	10,043	10,043
10°	9,870	9,880
20°	9,435	9,460
30°	8,709	8,707
40°	7,644	7,650
50°	6,259	6,275
60°	4,528	4,532
70°	2,523	2,514
80°	670	634
90°	18	6


Zonal Lumen Summary

Zone	Lumens	% Fixture
0° – 0°	948	3.3%
0° – 10°	3,679	13.0%
0° – 20°	7,864	27.7%
0° – 30°	12,973	45.8%
0° – 40°	18,320	64.6%
0° – 50°	23,099	81.5%
0° – 60°	26,503	93.5%
0° – 70°	28,029	98.9%
0° – 80°	28,232	99.6%
0° – 90°	109	0.4%
0° – 180°	28,341	100.0%

Cone of Light



HBRE-34L-4K (33,552 Lumens)




Candlepower Summary

	0°	90°
0°	11,925	11,925
10°	11,721	11,719
20°	11,195	11,183
30°	10,281	10,253
40°	8,994	8,978
50°	7,304	7,263
60°	5,236	5,143
70°	2,884	2,764
80°	775	680
90°	22	9

Zonal Lumen Summary


Zone	Lumens	% Fixture
0° – 0°	1,125	3.4%
0° – 10°	4,366	13.0%
0° – 20°	9,328	27.8%
0° – 30°	15,377	45.8%
0° – 40°	21,693	64.7%
0° – 50°	27,322	81.4%
0° – 60°	31,330	93.4%
0° – 70°	33,156	98.8%
0° – 80°	33,417	99.6%
0° – 90°	135	0.4%
0° – 180°	33,552	100.0%

Cone of Light




PHOTOMETRIC DATA


HBRE-14L-4K (14,497 Lumens)




HBRE-21L-4K (20,859 Lumens)



HBRE-28L-4K (28,341 Lumens)



HBRE-34L-4K (33,552 Lumens)



Foot Candles



Notes:

- Isofootcandle plots depict initial footcandles at grade.
- Gridlines represent units of mounting height of 25 feet.