

BOFRL SERIES

EasyLED Round Flat Bollards



The LEPG EasyLED Bollards with choice of optics are designed to replace HID lighting systems up to 70w MH or HPS. These fixtures are ideal for retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities.
Specifications and Features:

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Internal Ballast Tray for Easy Maintenance. Bollards Can Be Cut to Custom Lengths Upon Request.

Listing & Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750
IP65 Sealed LED Compartment.

Finish: Textured Architectural Bronze or Black Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

Style: Clear Prismatic Borosilicate Glass Refractor, Specially Designed Aluminum Cone Reflector or Internal Louvers

Lens: Clear Polycarbonate Vandal-Resistant Lens

Mounting Options: Mounting Kit with 8" Anchor Bolts, Included.
EasyLED LED: Aluminum Boards

Wattage: Array: 14.5w, System: 17w; (70w HID Equivalent)

Driver: Electronic Driver, 120-277V, 50/60Hz or 347V, 50/60Hz; Less Than 20% THD and PF>0.90. Standard Internal Surge Protection 2kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.


Warranty: 5-Year Warranty for -40°C to +40°C Environment.




Glass
EBOFGQ



LED Cone
Reflector Shown
with Glare Shield
EBOFRLQ



Louvers
EBOFLQ




Dimensions

Diameter (D)	7" (178mm)
Height (A)	41 1/8" (1,057mm)

Order Information Example:

Model	Optics	Wattage	Driver	CCT	Color	Height	Options
Model	Optics	Wattage	Driver	CCT	Color	Height	Options
EBOFGQ =Round Flat Top Bollard with Glass EBOFRLQ =Round Flat Top Bollard with LED Cone Reflector EBOFLQ =Round Flat Top Bollard with Louvers	C =Type III* F =Wide Beam Spread *BOFGQ and BOFRLQ only	1X15 =15w	U =120-277V C =347V	3K =3000K 4K =4000K 5K =5000K	Z =Bronze B =Black C =Custom (Consult Factory)	(Leave Blank) =42" Standard Height 36 =36" Height 30 =30" Height	SF =Single Fuse DF =Double Fuse SP =Surge Protection GF1 =GFCI Outlet, 15A, 120V GSB =180° Glare Shield, Black GSZ =180° Glare Shield, Bronze GSC =180° Glare Shield, Custom Color, Consult Factory BU =Battery Backup, 90 Minutes

Accessories & Replacement Parts:




*Shown Mounted


Mounting Accessories (Order Separately, Field Installed)		Replacement Parts (Order Separately, Field Installed)	
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts	BOLPC	Replacement Round Polycarbonate Vandal-Resistant Lens
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts	BORBASE*	Die Cast Base Plate with Powdercoat Finish Over a Chromate Conversion Coating.
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts	BOADP1	Adapter Plate with Gaskets for Outlet Boxes. Fits LEPC Round Bollards. Die Cast with Bronze Powdercoat Finish.
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts		
BOLRM	Root Mount Kit		*Specify Color: Z=Bronze, B=Black
BREBASE*	Bollard Retrofit Base Kit Adapts New Bollards to Most Existing Bolt Patterns. Fits all LEPC Bollards. Die Cast with Powdercoat Finish, Hardware Included. 11½" Dia. x 1½" H		For Replacement Battery Backup, see the LEPC LED Battery Backup Specification Sheet.

*Specify Color: Z=Bronze, B=Black, C=Custom (Consult Factory)

Photometric Data



EBOFGQF1X15U5K
Type V
Grid in feet, Mounting Height = 3.5 ft.



EBOFRLQF1X15U5K
Type V
Grid in feet, Mounting Height = 3.5 ft.

Photometric Performance

LED Board Watts	Drive Current (mA)	Input Watts	Optics	5000 CCT 80 CRI					4000 CCT 80 CRI					3000 CCT 80 CRI				
				Lumens	LPW	B	U	G	Lumens	LPW	B	U	G	Lumens	LPW	B	U	G
EasyLED 15w	116	17	BOFG Glass	1,125	66	1	3	1	1,080	64	1	3	1	905	53	1	3	1
			BOFL Louvers	778	46	1	2	1	747	44	1	2	1	689	41	1	2	1
			BOFRL Cone Reflector	1,519	89	1	3	1	1,458	86	1	3	1	1,225	72	1	3	1
			BOFRL Type III Optic	1,081	64	0	3	1	989	58	0	2	1	918	54	0	2	1

Projected Lumen Maintenance

Data shown for 5000 CCT			Compare to MH			
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L70@ 25°C
L70 Lumen Maintenance @ 25°C / 77°F	17	1.00	0.95	0.90	0.80	147,000
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L70@ 50°C
L70 Lumen Maintenance @ 50°C / 122°F	17	1.00	0.89	0.78	0.55	67,000
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L80@ 40°C
L80 Lumen Maintenance @ 40°C / 104°F	17	1.00	0.92	0.85	0.70	66,000

NOTES:

1. Projected per IESNA TM-21-11. Data references the extrapolated performance projections for the 116mA base model in a 25°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.
2. Compare to MH box indicates suggested Light Loss Factor (LLF) to be used when comparing to Metal Halide (MH) systems.

07.2019