

## ECAELXTE

### CHICAGO APPROVED EDGELIT ALUMINUM EXIT/STAIR SIGN

STANDARD



#### ILLUMINATION

- Ultra-bright, energy efficient, long-lasting white LEDs provide uniform illumination.
- UV stabilized, silk screened acrylic panels provide consistent, uniform illumination.

#### ELECTRICAL

- Dual 120V/277 voltage.
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing.
- 4.8V Long-life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 120-minute emergency illumination.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### MOUNTING

- Die-cast aluminum mounting canopy provided for universal top, end or back mount.

#### HOUSING

- Premium-grade, extruded aluminum housing (also available in optional white powder-coated finish).
- Single or double face configurations.

#### ORDERING INFORMATION

PRODUCT NUMBER: **ECAELXTEU** No of Faces: **L:** **H:** **B:** Signage/Arrows:

Model	No. of faces	Letter	Housing	Battery	Signage/Directional Arrows
ECAELXTEU	1 Single Face	RW Red On White	A Aluminum	(blank) AC-Only	-NA Exit No Arrow
	2 Double Face		W White	EM Battery Backup	-S-NA Stair No Arrow
					-DA Exit Double Arrow
					-S-DA Stair Double Arrow
					-RA <sup>1</sup> Exit Right Arrow
					-S-RA <sup>1</sup> Stair Right Arrow
					-LA <sup>1</sup> Exit Left arrow Stair
					-S-LA <sup>1</sup> Left Arrow Exit Left/
					-LARA <sup>2</sup> Right Arrow Stair
					-S-LARA <sup>2</sup> Left/Right Arrow

<sup>1</sup> Available in single face configuration only.

<sup>2</sup> Available in double face configuration only.



#### WARRANTY/LISTING

- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Meets city of Chicago requirements.
- Certified to CEC under Title 20 Regulations.
- Five year warranty on all electronics and housing. Battery prorated for five years.
- UL listed for damp locations (0° – 50°C)

#### DIMENSIONS

