

Job Name: _____
 Type: _____
 Part #: _____
 Notes: _____

ENYDXR

INCANDESCENT NEW YORK CITY COMPLIANT STEEL EMERGENCY UNIT

STANDARD



ILLUMINATION

- Adjustable, glare-free PAR-type lamp heads with 9.0 watt (on 6V models) and 12.0 watt (on 12V models) incandescent lamps.
- Field installable third lamp head included with the 27 watt and 50 watt models.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- Remote capacity of 14.0 watts standard on the 12V model.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal knockout pattern on the back for wall mount.
- Side and top knockouts for conduit feed applications.

HOUSING

- Premium-grade, extruded aluminum housing (also available in optional white powder-coated finish).
- Single or double face configurations.

ORDERING INFORMATION

PRODUCT NUMBER:	ENYDXR	Voltage:	No. of HEADS:	UW:	LW:	C:				
MODEL	VOLTAGE		No. of HEADS		UNIT WATTS		LAMP WATTS		COLOR	
ENYDXR	6	6 Volt	2	2 Heads	18	18 Watts ¹	9	9 Watts ¹	(blank)	Black
	12	12 Volt	3	3 Heads	27	27 Watts ¹	12	12 Watts ²	B	
					50	50 Watts ²				

¹ Available in 6V units only.

² Available in 12V units only.



HOUSING

- Durable powder-coated 20-gauge steel construction in white or black finish.
- Injection-molded engineering grade high-impact thermoplastic lamp heads to match housing finish.

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for dry locations (25°C).

DIMENSIONS

