

EXWL & EXCWL

Wet Location LED Exit Sign & Incandescent Emergency Polycarbonate Combo



Illumination

- Two fully adjustable 5.4 watt, glare-free incandescent lamp heads.
- High performance reflector and tempered glass lens for optimal light distribution.
- Ultra bright, energy efficient, long life Red or Green LED EXIT sign illumination.

Electrical

- Dual 120/277V.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 6V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Housing

- 5V A flame retardant, UV-stabilized polycarbonate gray finish.
- High-impact resistant, UV-stabilized polycarbonate clear lens.
- Corrosion-resistant enclosure engineering grade silicone gasket.
- Knockout's provided for conduit feed applications.
- EZ snap-out Chevron directional indicators.

Ordering Information

Product Number:

NF:

LC:

B:

O:

EXWL & EXCWL

Model

No. of FACES

LETTER COLOR

BATTERY

OPTIONS

Special voltage options available.

EXWL & EXCWL

(blank)

Single Face (standard)

R Red
G Green

EM Battery Backup (standard)

HTR Internal Heater



Mounting

- Mounting hardware provided for back surface wall mount.

Options

- HTR: Optional internal heater for cold temperature (-9°C – 40°C) applications.

Warranty/ Listing

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

Dimensions

