

EXDCC

All LED Exit & Emergency Die- Cast Aluminum Combo



Illumination

- Ultra bright, energy efficient, long life Red or Green LED Exit sign illumination.
- Two fully adjustable high performance premium grade, ultra bright white LED lamps.
- 3 watt (1 LED x 3 watts) per head.

Electrical

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 8.4V long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting

- Aluminum mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

Housing

- Unique design provides spec grade EXIT sign with LED lamp heads in one low profile housing.
- Premium-grade, extruded aluminum housing (also available in black or white powder-coated finishes).
- Field selectable knockout Chevron directional indicators.
- Quick-snap face plate closure.
- Unique design allows double face conversion in the field.

Ordering Information

* Special voltage options available.

Product Number: EXDCCU NF: LC: HC: FP: B: O:

| Model | No. of Face | Letter Color | Housing Color | Face Panel | Battery | Options |
|---------|--------------------------------|--------------|---------------|------------|-------------------|--------------------|
| EXDCC | 1 Single Face | R Red | W White | W White | EM Battery Backup | RC Remote Capacity |
| | 2 Double Face | G Green | B Black | B Black | | |
| | 3 Universal Single/Double Face | | A Aluminum | A Aluminum | | |
| 08.2019 | | | | | | |



Options

- RC: Remote capacity of up to 3.0 watts.

Warranty/ Listing

- Five year warranty on all electronics and housing. Battery proated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

Dimensions

