

ADCST

CUT-OFF LED WALLPACK LUMINAIRE



HEAVY-DUTY HOUSING

The DC150 is a Medium 14" Wallpack with a Die Cast Aluminum Body and Prismatic Borosilicate Glass Lens.

WET LOCATION, IP-65 RATED

Engineered and Constructed for Exterior Environments

EASY TO INSTALL MOUNTING

The DC150 can be Surface Mounted over an Existing 4" Outlet Box or Surface Wired through a 1/2" Conduit Entry. Additional Conduit entries Available for Photocells & other Components


120-277V STANDARD TYPE IV DISTRIBUTION

OPERATING TEMPERATURE -20C TO 40C

0C - 40C with EM Pack Option



PRODUCT DIMENSIONS



POWER
POWER FACTOR >0.90 - THD <20

PRODUCT SPECIFICATIONS

SYSTEM WATTAGE	NOMINAL WATTAGE	CCT	LUMENS	EFFICACY	DLC LISTING
12W	12.65	3000K	1,530.00	120.95	PREMIUM
12W	12.65	4000K	1,606.50	127.00	PREMIUM
12W	12.65	5000K	1,686.83	133.35	PREMIUM
24W	23.68	3000K	3,060.00	129.22	PREMIUM
24W	23.68	4000K	3,213.00	135.68	PREMIUM
24W	23.68	5000K	3,373.65	142.47	PREMIUM
36W	34.27	3000K	4,147.00	121.01	PREMIUM
36W	34.27	4000K	4,354.35	127.06	PREMIUM
36W	34.27	5000K	4,572.07	133.41	PREMIUM
48W	45.80	3000K	5,529.33	120.73	PREMIUM
48W	45.80	4000K	5,805.80	126.76	PREMIUM
48W	45.80	5000K	6,096.09	133.10	PREMIUM
60W	56.83	3000K	6,911.67	121.62	PREMIUM
60W	56.83	4000K	7,257.25	127.70	PREMIUM
60W	56.83	5000K	7,620.11	134.09	PREMIUM
72W	67.65	3000K	8,294.00	122.60	PREMIUM
72W	67.65	4000K	8,708.70	128.73	PREMIUM
72W	67.65	5000K	9,144.14	135.17	PREMIUM

PRODUCT APPLICATIONS

- Building Entrances Walkways
- Tunnels
- Loading Docks
- Bridges
- Stairwells

ORDERING GUIDE

MODEL	WATTAGE	COLOR TEMPERATURE (CCT)	HOUSING COLOR	OPTIONS & ACCESSORIES
DCSHM				
DCSHM	12W 12 WATTS 24W 24 WATTS 36W 36 WATTS 48W 48 WATTS 60W 60 WATTS 72W 72 WATTS	27K 2700K - WARM WHITE 30K 3000K - WARM WHITE 35K 3500K - NEUTRAL WHITE 40K 4000K - NEUTRAL WHITE 50K 5000K - COOL WHITE 55K 5500K - DAYLIGHT	BZ BRONZE (STANDARD) WH WHITE BL BLACK SL SILVER CC CUSTOM COLOR	MS MOTION SENSOR MS-DS2 MOTION SENSOR WITH BILEVEL DIMMING D1 0-10V DIMMING D2 STEP DIMMING (120V ONLY) EM EMERGENCY BATTERY PACK V1* 480/347V INPUT (120-277V STANDARD) *NOT AVAILABLE WITH EM OR MOTION SENSOR