

AKH45Q

EasyLED Large Bentley Kitty Hawk Area, Wall, and Flood Light



The LEPG AKH45Q luminaire is available in two wattages with a wide choice of mounting configurations and optical distributions designed to replace HID lighting systems from 250w to 1000w MH or HPS. Typical applications include general area, parking, flood, security, and accent lighting for retail centers, industrial parks, schools and universities, public transit and airports, office buildings and medical facilities. Mounting heights of 16 to 35 feet can be used based on light level and uniformity requirements.

Specifications and Features:

Housing:

Die Cast Aluminum Housing and Front Frame, Integral Heat Sinking and Driver Compartment. Photocell Adaptable. Nickel-Plated Stainless Steel Hardware.

Listing & Ratings:

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750; IP66 Sealed LED Compartment.

Finish:

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

Lens:

Tempered Clear Flat or SoftLED Flat Glass, or Tempered Clear Flat Prismatic Glass Lens.

Mounting Options:

Mounts with Kitty Hawk Arm, Adjustable Slipfitter, 2 3/4" Diameter Mounting Arm Adapter, Yoke, Two-Piece Bracket or Wall Mount Bracket. (Factory Installed)

EasyLED LED:

Aluminum Boards

Driver:

Electronic Driver, 120-277V, 50/60Hz or 347-480V, 50/60Hz; Less Than 20% THD and PF>0.90. Standard Internal Surge Protection 6kV. 0-10V Dimming Standard for a Dimming Range of 100% to 10%; Dimming Source Current is 150 Microamps.

Controls:

Fixtures Ordered with Factory-Installed Photocell or Motion Sensor Controls are Internally Wired for Switching and/or 1-10V Dimming Within the Housing. Remote Direct Wired Interface of 1-10V Dimming is Not Implied and May Not Be Available. Please Consult Factory. Fixtures are Tested with LEPG Controls and May Not Function Properly With Controls Supplied By Others. Fixtures are NOT Designed for Use with Line Voltage Dimmers.

Warranty:

5-Year Warranty for -40°C to +50°C Environment.

See Page 6 for Projected Lumen Maintenance Table.

Order Information:

Model	Optics/Beam	Wattage	Driver	CCT	Lens	Color	Mounting	Options
AKH45Q								
AKH45Q=Large Bentley Kitty Hawk Area, Wall, and Flood Light	A =Type I/NEMA 7H x 5V B =Type II/NEMA 7H x 6V C =Type III/NEMA 7H x 7V D =Type IV/NEMA 7H x 6V F =Type V/NEMA 7H x 7V I =Narrow Beam/NEMA 4H x 4V* *Use with 5K Model Only. See Page 4 & 6 for Distribution Information.	1X167 =167w 1X256 =256w	U =120-277V H =347-480V	3K =3000K* 4K =4000K 5K =5000K *Only for C & F Optics.	C =Standard Clear Flat Glass Lens S =SoftLED Flat Glass Lens P =Clear Flat Prismatic Glass Lens* *Use with Type V Optic Only.	Z =Bronze C =Custom (Consult Factory)	KA =Kitty Hawk Arm SF = Slipfitter MA = Mounting Arm Adapter Y =Yoke BR =Two-Piece Swivel Bracket WM =Wall Mount Bracket NM =No Mount	SF =Single Fuse (120-277V Only) DF =Double Fuse (120-277V Only) SP =Surge Protection M1 =Motion Sensor, IR for mounting heights of 20ft to 35ft M2 =Motion Sensor, IR for mounting heights of 18ft or less R3 =3-Pin Twist Lock Photocell Receptacle R5 =5-Pin Twist Lock Photocell Receptacle R7 =7-Pin ANSI C136.41—2013 Twist Lock Photocell Receptacle S23 =Internal Microwave Sensor with dimming for mounting heights of 35' or less (120-277V Only)




Shown with "KH" Kitty Hawk Arm Option on a Pole.



Shown with "WM" Wall Mount Bracket Option.



Shown with "SF" Slipfitter Mounting Option.



- Kitty Hawk Arm (KA):** 27 1/2" (699mm)
- Slipfitter (SF):** 29 1/4" (743mm)
- Mounting Arm Adaptor (MA):** 26 1/4" (664mm)
- Yoke (Y):** 26 1/4" (667mm)
- Bracket (BR):** 25 3/4" (654mm)

Dimensions

Width (D)	15 1/4" (400mm)	
Length (B)	22" (559mm)	Length with Mount (L)
Height (A)	4" (102mm)	

Job Name: _____

Type: _____

Part #: _____

Notes: _____

Mounting Options:



AKH45Q with Kitty Hawk Arm (KA)

Kitty Hawk Die-Cast Mounting Arm, Bronze Powdercoat Finish, Includes Hardware. Mounts Directly to Square Poles.



AKH45Q with Pole Mounting Arm Adaptor (MA)

Die-Cast Adaptor for 2 3/4" Horizontal Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.



AKH45Q with Yoke (Y)

Stamped Heavy-Duty Steel Yoke, Bronze Powdercoat Finish, Includes Hardware.



AKH45Q with "SF" External Mount Slipfitter (SF)

External Mount Die-Cast Adjustable Slipfitter for 2 3/4" Tenons, Bronze Powdercoat Finish, Includes Hardware.



AKH45Q with Two-Piece Swivel Bracket (BR)

Two-Piece Stamped Steel Adjustable Bracket, Bronze Powdercoat Finish, Includes Hardware.



AKH45Q with Wall Mount (WM)

Wall Bracket, Heavy-Duty Stamped Steel, Bronze Powdercoat Finish, Includes Hardware.

EPA (Effective Projected Area)

Shown with Large Kitty Hawk Arm mounting.

Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)	Configuration	EPA (Sq. Ft.)	Weight (Lbs.)
1	1.00	33 Lbs	2@180° Mount	2.00	66 Lbs	3@90° Mount	2.20	99 Lbs	4@90° Mount	2.20	132 Lbs
			2@90° Mount	1.36	66 Lbs	3@120° Mount	2.00	99 Lbs			

Accessories & Replacement Parts:



Mounting Accessories (Order Separately, Field Installed)

KH40RPZ	Die-Cast Adaptor for 4" to 6" Round Poles, Bronze Powdercoat Finish. Use with KH45A Kitty Hawk Mounting Arm only.
KH40WMZ	Die-Cast Wall Mount Adaptor, Bronze Powdercoat Finish. Use with KH45A Kitty Hawk Mounting Arm only.
PTSB1SZ	Single Pole Tenon Spoke Bracket, 2 3/4" Horizontal Mounting Arm, Bronze Powdercoat Finish, Includes Hardware.
PTSB290SZ	Twin Pole Tenon Spoke Bracket, 2 3/4" Horizontal 90° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.
PTSB2180SZ	Twin Pole Tenon Spoke Bracket, 2 3/4" Horizontal 180° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.
PTSB390SZ*	Triple Pole Tenon Spoke Bracket, 2 3/4" Horizontal 90° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.
PTSB3120SZ*	Triple Pole Tenon Spoke Bracket, 2 3/4" Horizontal 120° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.
PTSB490SZ*	Quad Pole Tenon Spoke Bracket, 2 3/4" Horizontal 90° Mounting Arms, Bronze Powdercoat Finish, Includes Hardware.

*Non-stock item. Consult factory for lead time.

Accessories (Order Separately, Field Installed)

P18131	Twist Lock Non-Shorting (Open) Cap Disconnects Service to Fixture for Temporary or Permanent Disabling (Fixture Always Off). IP65, 480V Maximum.
P18132	Twist Lock Shorting Cap Provides Fixed Service to Fixture (Fixture Always On). IP65, Rated Load 7200w Tungsten.
P18140	110-120VAC Instant Twist Lock Photocell
P18150	120VAC Time Delay Twist Lock Photocell
P18152	277VAC Time Delay Twist Lock Photocell
P18156	120-277VAC Universal Twist Lock Photocell
P18157	480VAC Time Delay Twist Lock Photocell. For 480V use only.
ACCHSG1Z	Die Cast Accessory Housing for Installing Sensors or Other Lighting Controls, Bronze Powdercoat Finish
KH45GSZ	Aluminum Glare/House Side Shield, Bronze Powdercoat Finish, Includes Hardware.
KH45WG	Wire Guard, Stainless Steel Construction, Includes Hardware.
ACCHSG3	Bronze Polycarbonate Housing for Installing Sensors, Includes Sensor Bracket and Gasket.

Replacement Parts (Order Separately, Field Installed)

KH45GL	Tempered Clear Flat Glass Lens.
KH45GLSS	SoftLED Flat Glass Lens
KH45GLP	Tempered Prismatic Flat Glass Lens.
KH45AZ	Kitty Hawk Mounting Arm, Mounts Directly to Square Poles, Bronze Powdercoat Finish
FL73SFXZ	External Mount Slipfitter, Die Cast, Bronze Powdercoat Finish
ALMAAZ	Pole Mounting Arm Adaptor, Fits 2 3/4" Arm, Includes Hardware, Bronze Powdercoat Finish
KH45YZ	Yoke, Stamped Heavy-Duty Steel, Bronze Powdercoat Finish
FL73BRZ	Two-Piece Swivel Bracket, Stamped Steel, Bronze Powdercoat Finish
WBR2Z	Wall Bracket, Heavy-Duty Stamped Steel, Bronze Powdercoat Finish, Includes Hardware.
P17117	Internal Microwave Sensor with Dimming, 120-277VAC, 50/60Hz. See P17117 Specification Page for Details.


Job Name: _____

Type: _____


Part #: _____

Notes: _____


Photometric Data




AKH45QA1X256U5KC
Type I
 Grid in MH
 MH=25 Feet




AKH45QB1X256U5KC
Type II
 Grid in MH
 MH=25 Feet



AKH45QC1X256U5K
C Type III
 Grid in MH
 MH=25 Feet



AKH45QD1X256U5KC
Type IV
 Grid in MH
 MH=25 Feet



AKH45QF1X256U5KC
Type V
 Grid in MH
 MH=25 Feet




Job Name: _____
 Type: _____
 Part #: _____
 Notes: _____


Photometric Performance

LED Board Watts	Drive Current (mA)	Input Watts	5000 CCT 80 CRI							4000 CCT 80 CRI				
				Optics	Lumens	LPW	B	U	G	Lumens	LPW	B	U	G
EasyLED 167w	525	179	A	Type I	22,487	126	4	0	3	21,644	121	4	0	3
			B	Type II	21,452	120	3	0	3	20,648	115	3	0	3
			C	Type III	23,566	132	3	0	3	22,682	127	3	0	3
			D	Type IV	23,888	134	3	0	4	22,992	129	3	0	4
			F	Type V	22,479	126	4	0	2	21,636	121	4	0	2
EasyLED 256w	525	275	A	Type I	34,471	125	5	0	3	33,178	121	5	0	3
			B	Type II	32,884	120	3	0	3	31,651	115	3	0	3
			C	Type III	36,125	132	4	0	4	34,770	127	4	0	4
			D	Type IV	29,808	109	3	0	4	28,690	104	3	0	4
			F	Type V	34,459	125	5	0	2	33,167	121	5	0	2


Photometric Data




AKH45QA1X256U5KC
 130°H x 70°V, NEMA 7H x 5V




AKH45QB1X256U5KC
 110°H x 30°V, NEMA 7H x 6V




AKH45QC1X256U5KC
 120°H x 70°V, NEMA 7H x 7V



AKH45QD1X256U5KC
 110°H x 50°V, NEMA 7H x 6V



AKH45QF1X256U5KC
 115°H x 110°V, NEMA 7H x 7V



AKH45QI1X256U5KC
 30°H x 30°V, NEMA 4H x 4V



Job Name: _____

Type: _____

Part #: _____

Notes: _____

Photometric Performance

LED Board Watts	Drive Current (mA)	Input Watts	Optics	5000 CCT 80 CRI		4000 CCT 80 CRI	
				Lumens	LPW	Lumens	LPW
EasyLED 167w	525	179	A 130°H x 70°V, NEMA 7H x 5V	22,472	126	21,629	121
			B 110°H x 30°V, NEMA 7H x 6V	21,481	120	20,675	116
			C 120°H x 70°V, NEMA 7H x 7V	23,397	131	22,520	126
			D 110°H x 30°V, NEMA 6H x 5V	23,625	132	22,739	127
			F 115°H x 110°V, NEMA 7H x 7V	22,537	126	21,692	121
			I 30°H x 30°V, NEMA 4H x 4V	24,160	135	23,252	130
EasyLED 256w	525	275	A 130°H x 70°V, NEMA 7H x 5V	34,448	125	33,156	121
			B 110°H x 30°V, NEMA 7H x 6V	32,928	120	31,694	115
			C 120°H x 70°V, NEMA 7H x 7V	35,866	131	34,521	126
			D 110°H x 50°V, NEMA 7H x 6V	29,483	107	28,377	103
			F 115°H x 110°V, NEMA 7H x 7V	34,547	126	33,252	121
			I 30°H x 30°V, NEMA 4H x 4V	37,035	135	35,647	130

Projected Lumen Maintenance

Data shown for 5000 CCT		Compare to MH				
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L70@ 25°C
L70 Lumen Maintenance @ 25°C / 77°F	275	1.00	0.97	0.95	0.90	290,000
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L70@ 50°C
L70 Lumen Maintenance @ 50°C / 122°F	275	1.00	0.94	0.88	0.76	84,000
TM-21-11	Input Watts	Initial	25,000 Hrs	50,000 Hrs	100,000 Hrs	Calculated L80@ 40°C
L80 Lumen Maintenance @ 40°C / 104°F	275	1.00	0.95	0.91	0.81	108,000

- NOTES:**
1. Projected per IESNA TM-21-11. Data references the extrapolated performance projections for the 525mA base model in a 25°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08.
 2. Compare to MH box indicates suggested Light Loss Factor (LLF) to be used when comparing to Metal Halide (MH) systems.