

## EWRE-4FT 4-Foot Slim Wraps

STANDARD



### FEATURES:

- Available in 3000k (warm white), 3500k (warm/neutral white) 4000k (neutral white) and 5000k (cool white) color temperatures.\*
- Long-life LEDs provide at least 50,000 hours of operation with at least 70% of initial lumen output (L70).\*\*
- Delivers 4,600 lumens at 4000k from 40 watts. 115 lumens per watt (LPW).
- Universal 120-277 AC voltage (50-60Hz) is standard.
- 0-10vdc, continuous dimming capability is standard.
- Power factor > 0.90.
- Total harmonic distortion < 20%.
- Color rendering index (Ra) > 80. Renders red colors (R9) > 0.
- LED color maintenance during the first 6,000 hours measured at < 0.004 on the CIE1976 chromaticity diagram.
- Polycarbonate lens resists cracking.
- Includes cover plate to cover junction boxes when surface-mounting the luminaire to ceiling-mounted junction boxes..
- Easy installation in new construction or retrofit applications.

### ORDERING INFORMATION:

Model	Length	Nominal Lumen Output	Color Temperature	
EWRE	4FT 4-Foot	4L 4k Lumens		
EWRE	4FT 4-Foot	4L 4k Lumens	3K	3000k
			35K	3500k
			4K	4000k
			5K	5000k



### WARRANTY & LISTINGS:

- cULus listed for damp locations in ambient temperatures from -20°C to 45°C (-4°F to 113°F).
  - DLC V5.0 standard approved.\*
  - Flicker-free per IEEE1789-2015 (low risk/ no observable effects of flicker at 100% light output level at 100% light output level).
  - Complies with FCC Part 15, class A
  - Complies with RoHS (Restriction on Hazardous Substances) requirements.
  - 5-year warranty of all electronics and housing.
- \* Excludes 3000k.

### DIMENSIONS:

