

## EEXST

### Steel LED Exit Sign



LISTED

#### FEATURES

Energy efficient LED technology,  
 Heavy-duty steel construction.  
 Steel knockout chevron directional indicators.  
 UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

#### ELECTRICAL

Dual 120V/277 voltage.  
 Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.  
 Maintenance free, rechargeable NiCad battery (EM model).  
 Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination.  
 Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.  
 LVD (low voltage disconnect) prevents battery from deep discharge.

#### MOUNTING

Universal surface mount, wall or ceiling, with EZ-snap thermoplastic mounting canopy, which snaps into place making installation quick & easy.

#### HOUSING

Durable, powder-coated 20-gauge steel construction.  
 Double face standard.  
 Universal knockout chevrons.

#### ORDERING INFORMATION

MODEL	FACE #	LETTER COLOR	HOUSING COLOR	BATTERY
EEXST	U2 - Universal Single/Double			
EEXST	U2 - Universal Single/Double	R - Red G - Green	B - Black W - White	Blank - AC only EM - NiCad Battery



#### ILLUMINATION

Ultra-bright, energy efficient, long-life Red or Green LED.

#### WARRANTY

Five year warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

#### DIMENSIONS

