


AOD LED Series Outdoor Billboard Sign Units

STANDARD



This billboard unit provides highlight levels with even distribution, for spot lighting. The unit is weather resistant and suitable for most outdoor applications.

Construction:

Housing is made of heavy gauge extruded aluminum with die cast end plates and splice box fittings. Housing interior is finished in a baked enamel finish for maximum reflectivity and durability. Splice box is threaded for 3/4" conduit and contains adjusting screws for housing. Lens is clear smooth slide-on acrylic that resists yellowing.

Electrical:

All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp and wet location.

Mounting:

Units are designed to be conduit mounted either individually, tandem, or in a continuous run.


Ordering Guide:



WARRANTY & LISTINGS

- 5-year warranty of all electronics and housing.
- UL Certified for damp location

DIMENSIONS



Fixture Length

# of Lamps	T5HO	Length
1 or 2	F54T5HO	53"
TANDEM		
Single or Double	F54T5HO	101"

For Tandem Units Multiply Unit above by 2

max weight= 11lbs/53" 15lbs/101"

Series	Size	Lumens		Color Temp	Options
AOD-LED					
*0-10v low voltage dimming standard per fixture	4 = 4FT	<u>4FT</u>		3K 35K 4K 5K	EMB = Emergency Ballast FR = Frosted lens over LED Boards
	6 = 6FT 8 = 8FT	3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W)	<u>8FT</u> 3220 (17W) 4480 (24W) 5705 (30W) 6910 (37W) 8640 (48W) 11797 (70W) 13820 (74W) 17280 (96W) 23594 (140W)		
*Higher and custom lumen packages available upon request					