

Job Name: _____

Type: _____

Part #: _____

Notes: _____

ELEDEM9

INCANDESCENT ADJ USTABLE RECESSED DOWNLIGHT EMERGENCY UNIT

STANDARD | OPTIONAL



ILLUMINATION

- Adjustable ultra bright 8 watt bi-pin halogen lamp in a gimbal trim.
- Sealed bean PAR36-type gimbal trim with smooth chrome-plated metalized reflector and plastic lens offers optimal light distribution.

ELECTRICAL

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents batter from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp head for minimum 90-mins emergency illumination.
- Fully automatic solid-state, two rate charger

MOUNTING

- Compatible with drop ceiling mount installation. Bar hangers included.

HOUSING

- 6" recessed housing with mounting bar hangers
- Impact-resistant thermoplastic adjustable gimbal trim.
- Junction bx with 3/4" knockouts for AC input.
- White or black trim securely attached to housing with spring clips.

OPTIONS

- LED: 1.5 watt LED Lamp

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA Local & State Codes.
- UL Listed for dry locations.

ORDERING INFORMATION

MODEL	HOUSING COLOR	LAMP OPTIONS
ELEDEM9	WHITE BLACK	(blank) LED 8.0 watt halogen lamp 1.5 watt LED lamp



DIMENSIONS

