

AAWL

All-Weather Wallpack - Low Profile



IP65



FEATURES & SPECIFICATIONS

CONSTRUCTION

- Die-cast aluminum housing
- Available in Bronze, White, Black, and Silver

OPTICAL

- UV-resistant, high-impact polycarbonate lens
- Minimum CRI of 70

ELECTRICAL

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Emergency Package (EP) option draws and additional 17W and includes self-test/self-diagnostic and a heater for cold weather operation to -25°C (-13°F)
- Standard photocontrol sensor for use in dusk to dawn applications that can be disabled to be used as and always on or switchable fixture.
- Optional PIR motion sensor (PIR) with up to 10' of detection and operational dusk to dawn. The light will activate when motion is detected in AC mode only and turn off after two minutes of inactivity.

BATTERY

- Maintenance-free NiCad Battery
- Operating temperatures: -25°C to 50°C (-13°F to 122°F)

INSTALLATION

- Universal pattern backplate provides 3" or 4" J-box mounting pattern with keyhole slots
- Can be surface mounted using the 1/2" conduit entry point at top of housing

WARRANTY

- 5 year warranty on all electronics and housing

ORDERING GUIDE

MODEL	Housing Color	Controls
AAWL		
All-Weather Wallpack Low Profile	BR - Bronze WH - White BK - Black SL - Silver	EP¹ - Emergency Package PIR² - PIR motion sensor



LISTINGS

- UL 924
- cULus Listed for Wet Locations
- IP65 rated
- State of California Title 24
- NFPA 101
- NFPA 70
- NEC
- UL Listed 90 minute emergency run time, 24 hour recharge time

PRODUCT DIMENSIONS

