

EBRK-LED

Architectural Trim 6"



ETL CLASSIFIED



Intertek (RETROFIT)

Intertek (NEW CONSTRUCTION)

Applications

6" architectural Recessed downlight retrofit solution with integrated LED power supply and thermal management system combined in a single compact unit designed to fit most standard 6" recessed cans. Also works in new construction applications.

Illumination

- Long life LEDs with up to 50,000 hours at 70% lumen maintenance.
- Choice of 3500K, 4000K, & 5000K color temperature with 80 CRI
- Produces 1500 lumens output from luminaire.
- Uses 1.18W high power, high quality LEDs.

Electrical

- Dimmable to 0-10V dimmers.

SYLVANIA	45167
Leviton Decora	IP710-LFZ
Lutron Diva	DVSTV-WH
Cooper	DF10P-C1

- Save 75% compared to incandescent sources.
- High efficiency driver with a power factor $\geq .90$ with input power of 120V-277V, 50-60Hz.
- Built-in LED Driver.
- Power consumption of 17 watts.
- Operation temperature of -20°C-40°C (-4°F-104°F).

Mounting

- Easy to install flex-cable into junction box.

Ordering Information

Product Number: EBRK-LED

M:

O:

KR:

L:

MODEL	OPTIONS	KELVIN RATING	LUMENS
EBRK-LED6A-BW-35K-ECO	BW	3500K	1500lm
EBRK-LED6A-BW-4K-ECO	BW	4000K	1500lm
EBRK-LED6A-BW-5K-ECO	BW	5000K	1500lm
ELED56-TRMPLT-ECO-SQ	Square	3500K	1500lm
ELED6A-TRMPLT-ECO-SPWHT	Silver/ White	3500K	1500lm



Housing

- Compatible with most 6" architectural housings or frames
- Compatible with insulated, non-insulated, and air-tight ceilings.
- Durable thermoplastic and aluminum construction.
- Flexible cable.
- Optional 6" square snap-on
- Optional 6" silver and white aluminum round trim

Warranty/ Listing

- Tested in accordance with IESNA LM79 & LM80.
- ETL Listed for wet location, US and Canada (new construction)
- ETL Classified for wet location, US and Canada (retrofit).
- Energy Star certified
- Passes FCC Class A.
- Meets State of California Title 24 requirements.
- Five year warranty on all electronics and housing.

Dimensions

